Product Code

7690N/5

Vibration Absorber
5/8"-16mm ODS



Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:
- HFC (R134a, R32, R404A, R407C, R410A, R507)
- HFO and HFO/HFC blends (R1234ze, R1234yf, R448A, R449A, R450A, R452A, R452B, R454B, R513A)
- HC (R290, R600, R600a, R1270)

Maximum allowable pressure PS = 50 bar.
Allowable temperatures TS = -80 to +140 °C
AISI 304 stainless steel connections.

Product Details

Connections ODS Ø [in.]	5/8"
Connections ODS Ø [mm]	16
PS [bar] TS [°C]-80 / +100	50
PS [bar] TS [°C]+120	49
TS [°C]+150	48
Package pcs	50

Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.
Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.