# Product Code

# 7690N/M28

Vibration Absorber
28mm ODS




## Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:
- HFC (R134a, R32, R404A, R407C, R410A, R507)
- HFO and HFO/HFC blends (R1234ze, R1234yf, R448A, R449A, R450A, R452A, R452B, R454B, R513A)
- HC (R290, R600, R600a, R1270)

Maximum allowable pressure PS = 50 bar.
Allowable temperatures TS = -80 to +140 °C
AISI 304 stainless steel connections.

## Product Details

| | |
|---|---|
| **Connections ODS Ø [in.]** | - |
| **Connections ODS Ø [mm]** | 28 |
| **PS [bar] TS [°C]-80 / +100** | 50 |
| **PS [bar] TS [°C]+120** | 49 |
| **TS [°C]+150** | 48 |
| **Package pcs** | 25 |

*Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.*
*Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.*